

www.mbmachineryconsulting.com

COD. 1704 - VIGANO' 2000 X 1.5 – 6 mm CUT TO LENGTH LINE

Manufacturer : Vigano (Italy), PLC: Siemens Built: 2000

Line available in 9 - 2023 Status: Still in production Strip width: 580 - 2000 mm Thickness: 1.5 - 6.0 mm Max coil weight: 30 tons

Max width 1250 mm up to S420MC

(max thickness 5 mm)

Length of sheet: 580 - 6000 mm Tolerance: +/- 1

Daily production: 80 tons

Line composition:

INPUT GROUP:

Double opposing uncoiler for coils up to 32 Tons, expandable from 500 to 700 mm input

pinch-roll, introduction table

GROUP OF LEVELLER

Levelling machine in fourth class with the possibility of acting on 7

back-up rollers to correct

the correct planarity of the material

CUTTING GROUP/Flyer shear

Measuring wheel and encoder give cutting consents to the shear mounted on a shear carriage

UNLOADING AREA:

Chain pantograph (6000 mm)

Two unloading chains that can be controlled both from the main pulpit and from the strapping station (6000 mm each); previously equipped with weight bridge. Please advise if further information is requested.

www.mbmachineryconsulting.com

Line composition:

GROUP OF INTRODUCTION:

Double counterposed uncoiler for 32 Ton max coil weight, expandible from 500 to 700 mm. Inlet pinch-roll, table of introduction.



LEVELLING GROUP

4-Hi Leveller, with possibility of adjustment of 7 counterrolls, to permit the correction of perfect planarity of the material.





www.mbmachineryconsulting.com

CUTTING STATION

The measuring wheel and encoder give the input of cutting to the shear that is mounted on the mobile section.



UNLOADING SECTION

Chain pantograph 6000 mm.





www.mbmachineryconsulting.com

Two unloadig chain conveyors that can be operated both by the main pulpit and by the strapping section (each one 6000 mm.) The first one is equipped by weight bridge.

